

iSee Video Cameras & Accessories for Remote Video Services

Wi-Fi IP Indoor & Outdoor Cameras



Live Video Delivered Online & to Cellphones & Smart Phones/Tablets with Google & iTunes Apps

Both Indoor & Outdoor Megapixel HD Camera/Kits now available



"The easiest, the first, the best"

More than 10 years ago, Napco pioneered remote video for RMR in the security industry. Used by the top of the Industry's Top 100, for years, it's field-proven, in tens of thousands of accounts. Unlike services sending still photos or using vulnerable WiFi networks, iSee Video simply, reliably & securely delivers live, high-res. video on-demand 24/7, on triggered events or archived for later review (even full-time recorded).

- Highest resolution remote video on the market! 25 frames per second @ VGA res. (640x480)
- Patented auto-detect and enrollment of wireless cameras- true plug-n-play
- Choice of Wi-Fi Cameras, pan & tilt, outdoor/waterproof or fixed IP, in all-inclusive turnkey keys with no sign up fees service charges for a whole year
- Put live video of your accounts' premise in the palm of your customers' hands with iPhones, Droids, Blackberrys, etc., or on their computer, and send them live video alerts anywhere in the world.
- **IVR - Unique Full-time recording option for up to 6 cameras for 90 days.** iSeeVideo Internet Video Recorders - Fully supervised, and an ideal replacement for unreliable DVRs, plus a new source of RMR.

www.napcosecurity.com

iSeeVideo  NAPCO



HERITAGE TECHNOLOGY SOLUTIONS

13600 S. Kenton Ave. • Crestwood, IL 60445

Phone: (708) 597-5005 • Fax: (708) 597-5091 • www.htspc.net



iSeeVideo Wi-Fi IP Indoor & Outdoor Cameras



IP Camera	Wireless Fixed IP	Wireless Pan/Tilt IP	Outdoor Wireless Fixed IP	Wireless Megapixel HD	Outdoor Wireless Megapixel HD
Model	ISVWLCAM	ISVWLCAMPT	ISVWLOCAM	ISVWLHDCAM	ISVWLOHD
Starter Kit	ISVWLKIT1	ISVWLPTKIT2	ISVWLKIT3	ISVWLHDKIT4	ISVWLKIT6
Video Image Sensor	Ominivision 7725 CMOS, 1/6" VGA Resolution	1/4" CMOS, VGA Resolution	1/5" CMOS, VGA Resolution	CMOS, 1/4" HD Resolution	CMOS, 1/4" HD Resolution
Lens:	F2.8 Fixed Focus, Effective Range: 0.2M to infinity	F2.0 Fixed Focus, Effective Range : 50cm to infinity	F2.0 Fixed Focus, Effective Range: 0.2M to infinity	F2.0 Fixed Focus Lens, Aperture:, Diagonal View Angle: 66° (Horizontal=57.8°, Vertical=37.8°	F2.0 Fixed Focus Lens, Aperture:, Diagonal View Angle: 66° (Horizontal=57.8°, Vertical=37.8°
Compression	MPEG-4	MPEG-4	H.264, MPEG-4	H.264, MPEG-4	H.264, MPEG-4
Resolution Support	640x480	640 x 480	640x480	720P HD (1280 x 720)	720P HD (1280 x 720)
Frame Rate, in VGA	30 fps	30 fps	30 fps	30 fps	30 fps
Image Control	AWB, Brightness	AWB, AGC, Sharpness, Brightness	AWB, AGC, Contrast, Brightness	AWB, AGC, Sharpness, Brightness	AWB, AGC, Sharpness, Brightness
Video options	Motion-Detection, Time Stamp, Text Overlay	Motion-Detection, Time Stamp, Text Overlay	Motion-Detection, Time Stamp, Text Overlay	4 Programmable Pixel Based Analytic Motion Detection Zones. PIR Motion Sensor Range: 15' (4.6m) with a viewing angle of 85° when installed at a height of 8'. Dual Technology Motion Detection Option, PIR and Pixel based trips required for event triggering. (Pats Pending)	4 Programmable Pixel Based Analytic Motion Detection Zones. PIR Motion Sensor Range: 15' (4.6m) with a viewing angle of 85° when installed at a height of 8'. Dual Technology Motion Detection Option, PIR and Pixel based trips required for event triggering. (Pats Pending)
Pan/Tilt Range		Pan: 126°, Tilt 64° + 53° View Angle, respectively			
Audio	Built-in Microphone	Built-in Microphone	Built-in Microphone	Built-in Microphone	Built-in Microphone
E-mail notification triggered by motion detection	Yes	Yes	Yes	Yes	Yes
Simultaneous Users	5	5	5	5	5
Wireless Standard	IEEE 802.11b and 802.11g	IEEE 802.11b and 802.11g	IEEE 802.11b/g/n	IEEE 802.11b/g/n	IEEE 802.11b/g/n
Range Indoor	50m	50m	50m	50m	50m
Outdoor rating			IP65 Waterproof rating		IP65 Waterproof rating
Infrared LEDs			8 IR LEDs with photoelectric cell control; Night Vision Filter	8 IR LEDs with photoelectric cell control; Night Vision 40' range	8 IR LEDs with photoelectric cell control; Night Vision 40' range
Encryptions	WPA, WPA2, 128bit WEP	WPA, WPA2, 128bit WEP	H.264, WPA, WPA2, 128bit WEP	128 Bit WPA	128 Bit WPA
NAPCO Automatic Secure Enrollment (Pats. Pending)	Yes	Yes	Yes	Yes	Yes
Working Temperature	-5°C to + 50°C	-5°C to + 50°C	-15° to 45°C	-15° to 50°C	-15° to 45°C
Power Adapter	5V / 2A, 100 / 240 VAC	5V / 2A, 100 / 240 VAC	5V/1A, 100/240 VAC	12VDC/1A, 100/240 VAC	12VDC/1A, 100/240 VAC
Certification	CE / FCC	CE / FCC	CE / FCC	CE / FCC	CE / FCC
Dimensions (HxWxD)	3.8 x 3.5 x 1.4"	5.7" x 3.8" x 3.1"	3.8" x 3.5" x 1.4"	3.6" x 2.4" x 1.4"	3.8" x 3.5" x 1.4"

Ordering Information for iSeeVideo Wireless Cameras/Kits & Accessories

ISVWLKIT1 Complete Wireless Camera Kit: One (1) 802.11 Wireless Fixed Camera, 640x480 hi-res, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLPTKIT2 Complete Wireless P/T Camera Kit: One (1) 802.11 Wireless Pan/Tilt Camera, 640x480 hi-res, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLKIT3 Complete Wireless Outdoor Camera Kit: One (1) 802.11 Wireless Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR motion detector, 6 IR LEDs with photo cell activation and night vision filter, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLHDKIT4 Complete Wireless Megapixel Camera Kit: Kit as above but with one (1) 802.11n Wireless HD Megapixel Camera, : 720p HD (1280x720), Infrared (IR), built in PIR (3.8"H x 2.5"W x 1.4"D (plus base, approx 3"sq.); power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLHDKIT6 Complete Outdoor Wireless Megapixel Camera Kit: Kit similar to above, but with one (1) 802.11n Wireless HD Megapixel Dual Antenna Outdoor Camera, IP65 Rated, : 720p HD (1280x720), Infrared (IR), built in PIR (3.8"H x 3.5"W x 1.4"D (plus base, approx 3"sq.); power adapter. Includes custom dealer website log-in screen and 12-months iSee Video Network access.

ISVWLCAM Add-on 802.11 Wireless Fixed Camera: 640x480 hi-res AC transformer (Kits support up to 6 cameras). Includes 12-months iSee Video Network access.

ISVWLCAMPT Add-on 802.11 Wireless Pan/Tilt Camera: 640x480 hi-res, power adapter (Kits support up to 6 cameras). Includes 12-months iSee Video Network access.

ISVWLOCAM Add-on Outdoor 802.11 Camera: Wireless Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR motion detector, 6 IR LEDs with photo cell activation and night vision filter, power adapter. (Kits support up to 6 cameras). Includes 12-months iSee Video Network access.

ISVWLHDCAM Add-on 802.11 Wireless HD Megapixel Camera with Infrared (IR) and built in PIR: 720p HD (1280x720), IR, PIR, AC transformer. Includes 12-months iSee Video Network access.

ISVWLHDCAM Add-on Outdoor 802.11 Megapixel Wireless Camera with IR and PIR: Similar to two prior models, but HD performance, in Outdoor, IP65 Rated Version. Dual antennas. 3.8" x 3.5" x 1.4"

ISV-REPT01 Optional Repeater will extend the range of cameras that are located away from the WAP (place approx. half way between WAP and farthest camera. One/Sys).

ISSE-IVR-250-1T Optional One-Terrabyte Internet Video Recorder Provides full time hi-res (640 x480) recording of up to 6 cameras for at least 90 days with full review and easy search functions. Fully, supervised; an ideal replacement for old DVRs, plus a new RMR stream.

ISSE-IVR-250 Optional Internet Video Recorder, as above, but recording of up to 6 cameras for 30 days.

www.napcosecurity.com/video.html

iSeeVideo 

333 Bayview Avenue, Amityville, NY 11701
1.800.645.9445 • www.napcosecurity.com